



Hi-Wall Premier Models			ASTG09LVCC	ASTG12LVCC	
Capacity	Cooling		KW	2.50	3.50
	Heating		KW	3.40	4.80
Input Power	Cooling (max)		KW	0.58 (1.24)	0.92 (1.42)
	Heating (max)		KW	0.73 (1.56)	1.11 (2.0)
Running Amps	Cooling		Amps	2.8	4.2
	Heating		Amps	3.5	5.0
Star Rating	Cooling			4.0	3.0
	Heating			4.5	4.0
Noise Level	Indoor Sound Pressure (High/Quite)	Cooling	dBa	41/21	42/21
		Heating	dBa	42/22	43/22
	Outdoor Sound Pressure Cooling/Heating		dBa	47/47	48/48
	Max outdoor Sound Pressure		dBa	64	66
Dimensions HxWxD	Indoor Unit		mm	293x790x22x	293x790x225
	Outdoor Unit		mm	540x660x290	540x790x290
Operating Range	Cooling		oCDB	-10 to 46	-10 to 46
	Heating		oCDB	-15 to 24	-15 to 24
Refrigerant				R410A	R410A

ASTG18LVCC	ASTG22LVCC	ASTG24LVCC	ASTG30LVCC	ASTG34LVCC
5.00	6.30	7.10	8.00	9.20
6.00	7.20	8.00	9.00	10.00
1.53 (2.03)	1.95 (2.75)	2.17 (2.86)	2.42 (3.15)	2.80 (3.54)
1.49 (3.19)	2.03 (4.18)	2.26 (4.06)	2.64 (3.53)	3.03 (3.57)
6.5	8.2	9.1	10.2	11.8
6.3	8.5	9.5	11.1	12.8
2.0	2.0	2.0	2.0	2.0
3.5	2.5	2.5	2.0	2.0
46/29	48/32	49/32	49/33	52/34
46/30	48/32	48/32	49/33	52/34
52/53	56/56	55/56	53/55	53/53
69	72	71	69	67
293x790x225	293x790x225	320x998x238	320x998x238	320x998x238
620x790x290	620x790x290	620x790x290	830x900x330	1290x900x330
-10 to 46	-10 to 46	-10 to 46	-10 to 46	-5 to 46
-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24
R410A	R410A	R410A	R410A	R410A